

# ROAD CLOSURE

**Bolton  
Council**

## NOTIFICATION OF TEMPORARY ROAD CLOSURE ROAD TRAFFIC REGULATION ACT 1984

STREET

**Slack Fold Lane**

DATES

**15 JUL 2024 for 3 days approx**

(end date and duration are subject to change)

REASON / WORKS

**works**

**Advertised public notice below  
Diversion plans (if available) are attached**

THE BOROUGH COUNCIL OF BOLTON  
ROAD TRAFFIC REGULATION ACT 1984 S.14  
SLACK FOLD LANE - TEMPORARY CLOSURE

The Council intends to make an order, operative from 15 July 2024 for 3 days approx, the effect of which will be to prohibit all traffic proceeding on Slack Fold Lane from Bayswater St to Plodder Ln. The Order will end after 18 months or on completion of the works whichever first occurs.

Bolton Council. 24 June 2024.



If your waste or recycling bins are due to be emptied during road or resurfacing works, please present them at the nearest accessible point. This will ensure that your bins can be emptied on the usual collection day.

**closures online at [bolton.gov.uk/trafficorders](https://bolton.gov.uk/trafficorders)**



Client:  
MORRISONS ELITE

Project: 1111165  
SLACK FOLD LANE  
HOLLINS  
BOLTON  
BL4 0LT

Title:  
ROAD CLOSURE  
DIVERSION

**DESIGN INPUTS** (FOR REFERENCE RELATE TO CONTROL DOCUMENT: F-012-DesignRefs Iss 1)

D1	<input type="checkbox"/>	D10 - OTHER? PLEASE STATE:
D2	<input type="checkbox"/>	
D3	<input checked="" type="checkbox"/>	
D4	<input type="checkbox"/>	
D5	<input checked="" type="checkbox"/>	
D10	<input type="checkbox"/>	

**Key:**

- Traffic sign
- Traffic cone/cylinder
- Traffic signals to Diagram 3000.1
- Pedestrian barrier
- Stop/Go board (P7023/P7024)
- Work Area
- Area of road closed
- Diversion Route
- Temporary vehicle restraint barrier

**This Drawing is the property of Dutton Traffic Management Services.**  
It MUST NOT be copied in part or sent to a third party without written permission.

**DETAIL B (B)**

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.  
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) 45° tapers have 1.5m spacing, no relaxations.  
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**DETAIL C1 (C1)**

Single/Dual carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Drawn: Martin Woulfe  
Checked: Gary Mainwaring

22/03/2024  
Rev:01

**DT25349-01-01**  
Original drawing size A3 - NTS

